



**Chung Kong Chemical Co. Ltd**

## **Technical Data Sheet**

---

**Battri-Guard 150** is a water-displacing solvent based rust preventive that is applied to aluminum, steel, stainless steel Battery cans by spray, immersion, or Hand wiping.

**Battri-Guard 150** is designed to leave a dry-to-touch finish on coated substrate. It is used as received and has very low odor. The protection is suitable for medium to long term corrosion prevention ,before and after filling of battery can. It also gives edge protection to Ni clad coatings such as Button cells.

**Battri-Guard 150** is recommended as a final dip on Battery Cans which are then coated with plastic labels.

No staining of the labels occurs. Adhesion of the label is good.

**Battri-Guard 150** will displace the rinse water to the bottom of the tank, where it can be periodically drawn off if cans are water wet on entry.

### **TYPICAL PROPERTIES**

Film Thickness..... 0.03 mls  
Coverage ..... approximately 3400 sq. ft./gallon  
Flash point ..... 143 °F

### **PHYSICAL DATA**

Specific gravity.....0.812  
Appearance and odor.....clear amber solution, non-viscous, solvent smell

### **CAUTION**

Harmful or fatal if swallowed. Contains petroleum distillates. Use with adequate ventilation. Avoid prolonged or repeated contact with skin. If swallowed, do not induce vomiting. Call physician immediately.

### **WARRANTY**

THE QUALITY OF THIS PRODUCT IS GUARANTEED ON SHIPMENT FROM OUR PLANT. IF THE USE RECOMMENDATIONS ARE FOLLOWED, DESIRED RESULTS WILL BE OBTAINED. SINCE THE USE OF OUR PRODUCTS IS BEYOND OUR CONTROL, NO GUARANTEE EXPRESSED OR IMPLIED IS MADE AS TO THE EFFECTS OF SUCH USE, OR THE RESULTS TO BE OBTAINED.