



Chung Kong Chemical Co. Ltd

Technical Data Sheet

Battri-Guard 200 is the result of the latest advances in Battery rust preventive technology. It is designed to be the final finish on Nickel clad, bare steel and Stainless Steel Battery components .

Battri-Guard 200 is a solvent-based, polar water-displacing rust preventive which can be applied by dipping, spraying or Hand Wiping. It will displace moisture on the metal surface, leaving a continuous film of Metal Guard[®] directly in contact with the metal surface. **Battri-Guard 200** is formulated to deposit a semi "dry-to-touch"; thin transparent corrosion resistant finish. It is used as received at room temperature.

Batti-Guard 200 is the first choice where **maximum corrosion resistance** is required for long Land and Sea Journeys.

Semi "dry to touch "resists staining of Plastic wrapping..

TYPICAL PROPERTIES

Film Thickness.....0.2l mils
Coverageapprox. 2,400 sq.ft/gallon
Water Displacement Test..... meets Mil Spec MIL-C-16173D, Grade 3
Corrosioin Test..... meets Mil Spec MIL-C-23411 and MIL-C-81309

PHYSICAL DATA

Flash point 149 °F
Specific gravity..... 0.821
Appearance and odor.....clear amber solution, non-viscous, solvent smell

CAUTION

Harmful or fatal if swallowed. Contains petroleum distillates. Use with adequate ventilation. Avoid prolonged or repeated contact with skin. If swallowed, do not induce vomiting. Call a physician immediately.

WARRANTY

THE QUALITY OF THIS PRODUCT IS GUARANTEED ON SHIPMENT FROM OUR PLANT. IF THE USE RECOMMENDATIONS ARE FOLLOWED, DESIRED RESULTS WILL BE OBTAINED. SINCE THE USE OF OUR PRODUCTS IS BEYOND OUR CONTROL, NO GUARANTEE EXPRESSED OR IMPLIED IS MADE AS TO THE EFFECTS OF SUCH USE, OR THE RESULTS TO BE OBTAINED.